

Horizontal Fiber Optic Splice Closure CH020

Optical Fiber Splice Closure TECHNICAL DATA SHEET



Product Description:

CH020 fiber optic splice closure is able to hold up to 8 splicing points, the fully rugged design enable it to work in the harshest environment, the mechanical locking system maintains the protection level at IP68 grade, it is suitable for direct buried, pipeline, wall mounted, manhole and handhole installation. 4 cable entrance(4-8)mm supports 2 cables entry from left and 2 cables.

Features:

- Water-proof design with IP-68 Protection level.
- Half design with easy access and tight water proof.
- Impact test: IK10, Pull Force :100N, Full rugged design.
- All stainless metal plate and anti- rusting bolts, nuts.
- Maximum splice capacity: 8 fibers.
- Suitable for the fusion splice or mechanical splice.
- Mechanical sealing with rubber protection tube.

Configuration

Material	Size	Max Capacity	Cable Ports	Sealing Method	Weight	Temperature
Polycarbonate	A*B*C (mm) 181*171*50	Splice 8 Fibers	4 Ports (4-6)mm 2 in 2 out	Mechanical sealing with thermoplastic rubber	0.8kg	-40~65

Application

- Direct buried installation
- Pole mounted installation
- Wall mounted installation
- Man hole and hand hole installation
- FTTH backbone layer

Standard Accessories

Installation bolts and nuts, protection sleeves, cable entry grommet, cable tube, Allen key .

Optional Accessories

Bracket for wall mounted, Pressure Valve, pole mounted kits