
Cat5e U/UTP Ethernet Bulk Cable — PVC

4 Pairs | 24 AWG Solid Bare Copper | 100 MHz | 305 m (1000 ft) Reel





1. GENERAL DESCRIPTION

Cat5e U/UTP bulk cable is designed for structured cabling and Ethernet networks up to 1000BASE-T (Gigabit Ethernet). It features four twisted pairs of solid pure bare copper conductors and a flame-retardant PVC jacket, making it suitable for general indoor installations in buildings, offices, data rooms and commercial premises. Supplied on a reel for easy, tangle-free pulling.

2. KEY FEATURES

- Pure bare copper solid conductors for low attenuation and stable long-run performance
- Flame-retardant PVC jacket: flexible, durable and easy to strip and terminate
- Supports Gigabit Ethernet and PoE / PoE+ (IEEE 802.3af / 802.3at)
- Optimised pair twist lengths for low crosstalk and high return-loss stability
- Supplied on a 305 m reel for smooth, tangle-free pay-out

3. APPLICATIONS

- Horizontal cabling in structured cabling systems (permanent link / channel)
- 10BASE-T, 100BASE-TX, 1000BASE-T Ethernet
- Voice, CCTV / IP cameras, access control, PoE devices (IEEE 802.3af/at)

4. APPLICABLE STANDARDS

- ANSI/TIA-568.2-D — Category 5e balanced twisted-pair cable
- ISO/IEC 11801 and IEC 61156-5 — Class D generic cabling
- IEC 60332-1 — Flame propagation (single vertical cable)

5. CABLE CONSTRUCTION

Conductor	Solid pure bare copper, 24 AWG (Ø 0.51 mm nominal)
Insulation	Solid HDPE (high-density polyethylene)
Pairs	4 twisted pairs, different twist lengths to minimise crosstalk

Pair Colour Code	Blue / White-Blue, Orange / White-Orange, Green / White-Green, Brown / White-Brown
Screening	None (U/UTP — unshielded)
Separator	[None / Cross filler (X-spline)]
Outer Jacket	Flame-retardant PVC — colour: [Grey / Blue / White]
Marking	CAT5e U/UTP 4P 24AWG PVC [standard] [metre marking]
Packing	305 m (1000 ft) on reel / pull box

Pair colour code

Pair	Conductor 1 (Tip)	Conductor 2 (Ring)
1	White / Blue	Blue
2	White / Orange	Orange
3	White / Green	Green
4	White / Brown	Brown

6. MECHANICAL & ENVIRONMENTAL

Overall Diameter (approx.)	[5.5 ± 0.2 mm]
Min. Bending Radius (installation)	4 × overall diameter
Max. Pulling Tension	110 N (25 lbf)
Operating Temperature	[-20 °C to +60 °C]
Installation Temperature	[0 °C to +50 °C]
Flame Retardancy	IEC 60332-1

7. ELECTRICAL CHARACTERISTICS (AT 20 °C)

Characteristic Impedance (1–100 MHz)	100 Ω ± 15 Ω
Max. DC Resistance (per conductor)	93.8 Ω/km (9.38 Ω/100 m)
Max. DC Resistance Unbalance	5 %
Max. Mutual Capacitance (1 kHz)	5.6 nF/100 m
Max. Capacitance Unbalance (pair to ground)	330 pF/100 m
Max. Propagation Delay (100 MHz)	538 ns/100 m
Max. Delay Skew	45 ns/100 m
Min. ACR-F / PS ACR-F (100 MHz)	23.8 dB / 20.8 dB per 100 m
Nominal Velocity of Propagation (NVP)	[~ 0.65]
Max. Operating Voltage	[72 V]
Dielectric Strength (DC, 1 min)	[1.0 kV]

8. TRANSMISSION PERFORMANCE (PER 100 M)

Frequency (MHz)	Insertion Loss — max (dB)	NEXT — min (dB)	PS NEXT — min (dB)
1	2.0	65.3	62.3
4	4.1	56.3	53.3
10	6.5	50.3	47.3
16	8.2	47.2	44.2
31.25	11.7	42.9	39.9
62.5	17.0	38.4	35.4
100	22.0	35.3	32.3

9. INSTALLATION & HANDLING GUIDELINES

- Do not exceed the max. pulling tension (110 N) or the min. bending radius (4 × OD).
- Avoid kinks, sharp bends, crushing and over-tight cable ties.
- Keep separation from power cables according to local wiring standards (EN 50174-2 / TIA-569).
- Untwist pairs by no more than 13 mm (0.5 in) at termination points.
- Test every installed link with a certified cable tester (Cat5e permanent link).