# Horizontal Single Sided Cable Manager, 1RU, 5 D-Rings

**D-Ring Manager | 1RU / 19 in | Single Sided**



## 1. GENERAL DESCRIPTION

This 1RU horizontal cable manager is a steel panel with five rounded D-rings for supporting and organizing patch cords in EIA 19 in racks and cabinets. D-ring management is one of the most basic and flexible forms of rack cable management, and the five rings hold large quantities of copper and fiber patch cables of all types and sizes. The single sided design keeps the rack neat and easy to maintain.

## 2. KEY FEATURES

- 5 rounded, radius-edged D-rings protect cables from nicks and wear
- Easy access to cables for moves, adds and changes
- Cold-rolled steel panel with black powder coat for lasting durability and rust resistance
- Accommodates large quantities of copper and fiber patch cables
- Compact 1RU body, 88 mm deep

## 3. APPLICATIONS

- Organizing patch cords between patch panels and switches
- Horizontal cable management in network and server racks
- Cable routing in data centers and telecom rooms
- Tidy, accessible rack cabling for installation and maintenance

## 4. COMPATIBLE RACKS & CABLES

- EIA 19 in racks and cabinets
- Rack space: 1RU (44 mm)
- Cables: copper and fiber patch cables of all types and sizes
- Not for vertical cable management or cable bundles above the rated capacity

## 5. SPECIFICATIONS

| | |
|---|---|
| **Model** | Horizontal Single Sided Cable Manager, 1RU, 5 D-Rings [model code CMH-5DR1U-N — confirm] |
| **Type** | Horizontal single sided D-ring cable manager |
| **Rack Space** | 1RU (44 mm) |
| **Rack Width** | 19 in (EIA) racks and cabinets |
| **D-rings** | 5 pcs, rounded, radius-edged [material ABS — confirm] |
| **Panel Material** | Cold-rolled steel, powder-coated |

| | |
|---|---|
| **Color** | Black |
| **Dimensions (H × W × D)** | 44 × 483 × 88 mm (1.73 × 19 × 3.46 in) [confirm depth] |
| **Supplied With** | [Cable manager with mounting hardware — confirm] |

## 6. INSTALLATION & MAINTENANCE

- Mount the manager in the required 1RU position in the 19 in rack using the rack screws.
- Route the cables through the D-rings, keeping to the minimum bend radius of the cables.
- Do not overfill the D-rings or exceed the rated capacity.
- Do not use the manager to bear the weight of equipment.
- Keep the panel and D-rings free of dust; wipe clean with a dry cloth.